THIS SPECIFICATION IS THE PROPERTY OF BOE HF AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE HF AND MUST BE RETURNED TO BOE HF UPON ITS REQUEST SPEC. NUMBER PRODUCT GROUP REV. ISSUE DATE PAGE TFT- LCD P0 2020.10 1 OF 31

B3 GV185FHM-N10 Product Specification Rev.P0

SUPPLIER	HEFEI BOE Optoelectronics Technology CO., LTD
FG-Code	GV185FHM-N10-DM30

ITEM	BUYER SIGNATURE DATE

ITEM SUPPLIER SIGNATURE	DATE
Prepared	
Reviewed	
Approved	

PROPRIETARY NOTE THIS SPECIFICATION IS THE PROPERTY OF BOE HF AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE HF AND MUST BE RETURNED TO BOE HF UPON ITS REQUEST SPEC. NUMBER PRODUCT GROUP **ISSUE DATE** REV. PAGE OF 31 TFT- LCD REV. ECN NO. **DESCRIPTION OF CHANGES DATE PREPARED** ** 2020.10.15 Initial Release P0


PROPRIETARY NOTE THIS SPECIFICATION IS THE PROPERTY OF BOE HF AND SHALL NOT BE REPRODUCED OR COPIED WITHOUT THE WRITTEN PERMISSION OF BOE HF AND MUST BE RETURNED TO BOE HF UPON ITS REQUEST



SPEC. NUMBER PRODUCT GROUP REV. ISSUE DATE PAGE
TFT- LCD OF 31

Contents


No.	Items	Page
1.0	General Description	4
2.0	Absolute Maximum ratings	6
3.0	Electrical specifications.	7
4.0	Interface Connection	10
5.0	Signal Timing Specifications	13
6.0	Signal Timing Waveforms Of Interface Signal	15
7.0	Power Sequence	17
8.0	Optical specifications.	18
9.0	Mechanical Outline Dimension	22
10.0	Reliability Test	24
11.0	Precautions	25
12.0	Label	29
13.0	Packing information	31



PRODUCT GROUP	REV	ISSUE DATE
TFT LCD PRODUCT	P0	2019.04.16

1.0 GENERAL DESCRIPTION

GV185FHM-N10-DM30 is a color active matrix TFT LCD module using amorphous silicon TFT's (Thin Film Transistors) as an active switching devices. This module has a 18.5 inch diagonally measured active area with FHD resolutions (1920 horizontal by 1080 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7 M colors.



1.0.2 Features

- LED back-light
- LVDS interface
- RoHS Compliant
- 16.7M color depth

1.0.3 Application

• Video Phone/IP Phone/Smart Key/ e-cigarettes etc.

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	4 OF 31

DAS-RD-2020006-O



 REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

1.0.4 General Specification

< Table 1. General Specifications >

Parameter	Specification(15inch 参考)	Unit	Remarks
Active area	408.96 (H) × 230.04(V)	mm	
Number of pixels	1920(H) × 1080(V)	Pixels	
Pixel pitch	0.213(H) × 0.213 (V)	mm	
Pixel arrangement	RGB Vertical stripe		
Display colors	16.7M(8bit)	Colors	
Display mode	Normally Black		
Dimensional outline	430.4 (H) × 254.6(V) × 12(D) typ.	mm	
Weight	1800	g	
Surface treatment	AG25 , 3H		
Back-light	Edge side, 1-LED Lighting Bar Type		44*LED

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	5 OF 31



PRODUCT GROUP	REV	ISSUE DATE
TFT LCD PRODUCT	P0	2019.04.16

2.0 ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit. The operational and non-operational maximum voltage and current values are listed in Table 2.

< Table 3. Environment Absolute Maximum Ratings>


[Ta =25 ± 2 °C]

Parameter	Symbol	Min.	Type.	Max.	Unit	Remarks
Back-light Power Supply Voltage	HV _{DDOUT}	1	33V	1	٧	
Back-light LED Current	I _{HVDD}		360		mA	Ta = 25 ℃ Note 1&2
Back-light LED Reverse Voltage	V_R		-		V	

Note:

- 1. These range above is maximum value not the actual operating temperature . Actual Operating temperature is no more than $\underline{40}^{\circ}\text{C}$ and temperature refers to the LCM surface temperature ;
- 2.BOE is not responsible for product problems beyond the use conditions.
- 3. When the ambient temperature is T °C, the surface temperature of Panel can not exceed (T+15)°C.

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	6 OF 31



PRODUCT GROUP	REV	ISSUE DATE
TFT LCD PRODUCT	P0	2019.04.16

3.0 ELECTRICAL SPECIFICATIONS

3.0.1 TFT LCD Module

< Table 4. LCD Module Electrical Specifications >

[Ta = 25 ± 2 °C]

Parameter	Symbol	Values			Unit	Notes	
		Min	Тур	Max			
Power Supply Input Voltage	V_{DD}	4	5	6	V	Note 1	
Power Supply Current	I _{DD}	-	500		mA	Note i	
LED Driver Power Supply Voltage	H _{VDD}	10.8	12	12.6	V		
LED Driver Power Supply Current	I _{HVDD}		TBD		mA	Note 2	
LED Power Consumption	P _{LED}		TBD		W		
Positive-going Input Threshold Voltage	V _{IT+}	1		+100	mV	Vcom = 1.2V	
Negative-going Input Threshold Voltage	V _{IT-}	-100		-	mV	typ.	
Differential input common mode voltage	V_{com}		1.2		V	V _{IH} =100mV, V _{IL} =-100mV	

Notes: 1. The supply voltage is measured and specified at the interface connector of LCM. The current draw and power consumption specified is for 3.3V at 25 °C Max value at Black Pattern

2. Calculated value for reference $I_{LED} \times V_{LED} \div 0.85 = P_{LED}$

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	7 OF 31



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

3.1 Back-light Unit

< Table 6. LED Driving guideline specifications >

Ta=25+/-2°C

	Parameter		Min.	Тур.	Max.	Unit	Remarks
Power supply ack light	y voltage for B	V_{LED}		12		V	
Power supply ack light	y Current for B	I _{LED}	-	TBD	-	mA	
Power supply	y for Back light	P _{LED}		TBD		W	Note 1
EN Control	Backlight on	V_{ENH}	2.5	1	1	٧	EN logic high v oltage
Level	Backlight off	V_{ENL}	1	1	0.8	V	EN logic low vol tage
PWM Cont	PWM High L evel	V_{PML}	2.5	1	1	V	
rol Level	PWM Low Le vel	V_{PML}	1	1	0.8	V	
PWM Contro	l Frequency	F _{PWM}	0.12	-	1	KHz	
Duty Ratio		-	5	-	100	%	

Notes : 1. Calculator Value for reference $I_{LED} \times V_{LED} = P_{LED}$

2. The LED Life-time define as the estimated time to 50% degradation of initial luminous under the condition of the ambient temperature of 25°C.

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	8 OF 31



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

4.0 INTERFACE CONNECTION.

4.0.1 Electrical Interface Connection

The electronics interface connector IS100-L30O-C23(UJU).


The LED connector is CI4205M2HRD-NH

The connector interface pin assignments are listed in Table 7 and 8.

<Table 7. Pin Assignments for the Interface Connector>

Pin No.	Symbol	Description	remark
1	RxOIN0-	LVDS data input	
2	RxOIN0+	LVDS data input	
3	RxOIN1-	LVDS data input	
4	RxOIN1+	LVDS data input	
5	RxOIN2-	LVDS data input	
6	RxOIN2+	LVDS data input	
7	VSS	Ground	
8	RxOCLKIN-	LVDS clock input	
9	RxOCLKIN+	LVDS clock input	
10	RxOIN3-	LVDS data input	
11	RxOIN3+	LVDS data input	
12	RxEIN0-	LVDS data input	
13	RxEIN0+	LVDS data input	
14	VSS	Ground	
15	RxEIN1-	LVDS data input	
16	RxEIN1+	LVDS clock input	
17	VSS	Ground	
18	RxEIN2-	LVDS clock input	
19	RxEIN2+	LVDS clock input	
20	RxECLKIN-	LVDS clock input	
21	RxECLKIN+	LVDS clock input	
22	RxEIN3-	LVDS clock input	
23	RxEIN3+	LVDS clock input	
24	VSS	Ground	

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	9 OF 31



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

Pin No.	Symbol	Description	remark
25	SCL	I2C BUS	
26	SDA	I2C BUS	
27	WP	EEPROM write EN	
28	VCC	Power supply(5V)	
29	VCC	Power supply(5V)	
30	VCC	Power supply(5V)	

<Table 8. Pin Assignments for the LED Connector>

Terminal	Symbol	Functions
Pin No.	Symbol	Description
1	VCC	12V
2	GND	GND
3	Enable	5V-On / 0V-Off
4	Dimming	PWM Dimming
5	NC	No Connection

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	10 OF 31



REV

ISSUE DATE


TFT LCD PRODUCT

P0

2019.04.16


4.2 Data Input Format

Figure 5. Pixel Format



Display Position of Input Data (V-H)

Figure 6. Scan direction



SPEC. NUMBER
S801-5126

PAGE 11 OF 31



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

5.0 SIGNAL TIMING SPECIFICATION

5.0.1 The XX-FG code is operated by the DE only. (以19inch为例,需根据具体项目变更)

						•	
Item	Symbols		Min	Тур	Max	Unit	Note
	Period	tCLK	9.5	TBD	25	ns	
DCLK	Frequency	-	40	-	105	MHz	
	Period	tHP	990	1040		tCLK	
Hsync	Horizontal Valid	tHV		960		tCLK	
	Horizontal Blank	tHB	30	80		tCLK	
	Period	tVP	1100	1125	1138	tHP	
Vsync	Vertical Valid	tVV		1080		tHP	
v sync	Vertical Blank	tVB	30	45	58	tHP	
	Frequency	fV		60		Hz	
LVDS R eceiver c lock	Input spread spect rum ratio	SSr		TBD		%	

Note: The DCLK range at last line of V-blanking should be set in 0-H-active/2.

SPEC. NUMBER
S801-5126



REV

ISSUE DATE

TFT LCD PRODUCT

P0


2019.04.16

5.02 LVDS Rx Interface Timing Parameter

The specification of the LVDS Rx interface timing parameter is shown in Table 4.

<Table 9. LVDS Rx Interface Timing Specification>

Item	Symbol	Min	Тур	Max	Unit	Remark
CLKIN Period	tRCIP	9.5		25	nsec	
Input Data 0	tRIP1	-0.4	0.0	+0.4	nsec	
Input Data 1	tRIP0	tRCIP/7-0.4	tRCIP/7	tRCIP/7+0.4	nsec	
Input Data 2	tRIP6	2 ×tRCIP/7-0.4	2 ×tRCIP/7	2 ×tRCIP/7+0.4	nsec	
Input Data 3	tRIP5	3 ×tRCIP/7-0.4	3 ×tRCIP/7	3 ×tRCIP/7+0.4	nsec	
Input Data 4	tRIP4	4 ×tRCIP/7-0.4	4 ×tRCIP/7	4 ×tRCIP/7+0.4	nsec	
Input Data 5	tRIP3	5 ×tRCIP/7-0.4	5 ×tRCIP/7	5 ×tRCIP/7+0.4	nsec	
Input Data 6	tRIP2	6 ×tRCIP/7-0.4	6 ×tRCIP/7	6 ×tRCIP/7+0.4	nsec	



SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	13 OF 31



REV

ISSUE DATE


TFT LCD PRODUCT

P0

2019.04.16


6. SIGNAL TIMING WAVEFORMS OF INTERFACE SIGNAL

6.01 Sync Timing Waveforms




- 1) Need over 3 H-sync during V-Sync Low
- 2) Fix H-Sync width from V-Sync falling edge to first rising edge

6.02 Vertical Timing Waveforms



SPEC. NUMBER
S801-5126



REV


ISSUE DATE


TFT LCD PRODUCT

P0

2019.04.16

6.03 Horizontal Timing Waveforms





SPEC. NUMBER	SPEC TITLE		PAGE
S801-5126	XX产品 FG-code	Product Specification	15 OF 31



REV

ISSUE DATE


TFT LCD PRODUCT

P0

2019.04.16

7.0 POWER SEQUENCE

To prevent a latch-up or DC operation of the LCD module, the power on/off seq uence shall be as shown in below



Danamatan		Values				
Parameter	Min	Тур	Max	Units		
T1	0	-	10	ms		
T2	0	-	50	ms		
Т3	200	-	-	ms		
T4	500	-	-	ms		
T5	0	-	50	ms		
Т6	0	-	10	ms		
Т7	500	-	-	ms		

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	16 OF 31

	•	-	-		-
H	≺	1	- 1	H	-0
		1	1		
			_		

PRODUCT GROUP	REV	ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

8.0 OPTICAL SPECIFICATION

8.0.1 Overview

The test of view angle range shall be measured in a dark room (ambient luminance \leq 1lux and temperature = $25\pm2^{\circ}$ C) with the equipment of Luminance meter system (Goniometer system and TOPCON CS2000/CA310) and test unit shall be located at an approximate distance 50cm from the LCD surface at a viewing angle of θ and Φ equal to 0° . We refer to $\theta\emptyset=0$ (= $\theta3$) as the 3 o'clock direction (the "right"), θ $\emptyset=90$ (= $\theta12$) as the 12 o'clock direction ("upward"), θ $\emptyset=180$ (= $\theta9$) as the 9 o'clock direction ("left") and θ $\emptyset=270$ (= $\theta6$) as the 6 o'clock direction ("bottom"). While scanning θ and/or \emptyset , the center of the measuring spot on the Display surface shall stay fixed. The luminance, color and uniformity (etc) should be tested by CS2000/CA310. The backlight should be operating for 10 minutes prior to measurement. VDD shall be 3.3 \pm 0.3V at 25°C. Optimum viewing angle direction is 6 'clock

<Table 10. Optical Specifications>

Parameter		Symbol	Condition	Min.	Тур.	Max.	Unit	Remark	
	Horizontal		Θ_3		80	85	-	Deg.	
Viewing Angle		Ullai	Θ_9	CR > 10	80	85		Deg.	Note 1
range	Verti	ical	Θ ₁₂	CK > 10	80	85		Deg.	
	VEILI	ICai	Θ_6		80	85		Deg.	
Luminance Co	ntrast	ratio	CR	Θ = 0°	700	1000			Note 2
Luminance of White	Cen	iter	Y _w		280	350	1	cd/m ²	Note 3
White Lumina nce uniformity	9 Po	ints	ΔΥ9	Θ = 0°	80	85	-	%	Note 4
Color Gamut	NTS	SC	CIE1931	Θ = 0°	65	70	-	%	
Reproduction	300	.,	Wx	0 00	Тур	0.306	Тур		Note 5
of color	White		Wy	Θ = 0°	-0.05	0.320	+0.05		
Response Time			Tr+Td	Ta= 25° C Θ = 0°	-	30	35	ms	Note 6
SPEC NUMBER SPEC TITLE								PAGE	

SPEC. NUMBER **\$801-5126**

SPEC TITLE

XX产品 FG-code Product Specification

PAGE 17 OF 31

BOE	PRODUCT GROUP	REV	ISSUE DATE
$D\subseteqL$	TFT LCD PRODUCT	P0	2019.04.16

- Notes: 1. Viewing angle is the angle at which the contrast ratio is greater than 10. The viewing angles are determined for the horizontal or 3, 9 o'clock direction and the vertical or 6, 12 o'clock direction with respect to the optical axis which is normal to the LCD surface (see FIGURE 1).
 - 2. Contrast measurements shall be made at viewing angle of Θ = 0 and at the center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white, then to the dark (black) state . (see FIGURE 1) Luminance Contrast Ratio (CR) is defined mathematically.

- 3. Luminance of white is defined as luminance values of center of the LCD surface. Luminance shall be measured with all pixels in the view field set first to white. This measurement shall be taken at the locations shown in FIGURE 2 for a total of the measurements per display. The luminance is measured by CS2000/CA310 when the LED current is set at 60mA.
- 4. The White luminance uniformity on LCD surface is then expressed as : $\Delta Y = Minimum Luminance of 9 Points or 5 points / Maximum Luminance of 9 Points or 5 points (See FIGURE 2).$
- 5. The color chromaticity coordinates specified in Table 5. shall be calculated from the spectral data measured with all pixels first in red, green, blue and white. Measurements shall be made at the center of the panel.
- 6. The electro-optical response time measurements shall be made as FIGURE 3 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Tr, and 90% to 10% is Td.

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	18 OF 31

DAS-RD-2020006-O A4(210 X 297)



PRODUCT	GROUP
---------	-------

REV

ISSUE DATE


TFT LCD PRODUCT

P0

2019.04.16


8.0.2 Optical measurements

Figure 1. Measurement Set Up



View angel range, uniformity, etc. measurement setup Flicker, measurement setup

Figure 2. White Luminance and Uniformity Measurement Locations (9 points)



Luminance of white is defined as luminance values of center of the LCD surface. L uminance shall be measured with all pixels in the view field set first to white. This m easurement shall be taken at the locations shown in FIGURE 2 for a total of the me asurements per display.

The White luminance uniformity on LCD surface is then expressed as : $\Delta Y9 = Mini$ mum Luminance of 9 points / Maximum Luminance of 9 points (see FIGURE 2).

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	19 OF 31



REV


ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16





The electro-optical response time measurements shall be made as shown in FIG URE 3 by switching the "data" input signal ON and OFF. The times needed for the luminance to change from 10% to 90% is Tr and 90% to 10% is Td.

SPEC. NUMBER	
S801-5126	



REV

ISSUE DATE


TFT LCD PRODUCT


P0

2019.04.16

9.0 MECHANICAL OUTLINE DIMENSION

Figure 1. TFT-LCD Module Outline Dimension (Front View)






NOTE:

- 1. BLACK LIGHT: LED WHITE;
- LCM_BRIGHTNESS(CENTER_POINT):280cd/m²(Min),350cd/m²(
- 2. GENERAL TOLERANCE: ±0.5mm;
- 3. CRITICAL CONTRAL POINT REFERENCED DIMENSION ();
- 4. CONFORMITY WITH ROHS AND HALOGEN FREE;
- 5. OPERATING TEMPERATURE: -20°C(Min.), 70°C(Max.);
- 6. STORAGE TEMPERATURE: −30°C(Min.), 80°C(Max.);
- 7. LCM HOMOCENEITY: 80%(min), 85%(typ),L255@9 Point;
- 8. CN1: IS100-L300-C23 CN2&CN3: CI4216S;

SPEC. NUMBER
S801-5126



PRODUCT GROUP	PRODUCT	GROUP
---------------	----------------	-------

REV


ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

Figure 2. TFT-LCD Module Outline Dimensions (Rear view)



SPEC. NUMBER
S801-5126



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

10.0 RELIABILITY TEST (以客户规格为主,若客户无具体规格,以厂内标准为准)

The Reliability test items and its conditions are shown in below.

<Table 11. Reliability test>

No	Test Items	Conditions	Remark
1	High temperature storage test	Ta = 80° C, 240 hrs	The test result shall b
2	Low temperature storage test	Ta = -30 °C, 240 hrs	e evaluated after the
3	High temperature operation te st	Ta = 70°C, 240 hrs	sample has been left at room temperature and humidity for 2 h
4	Low temperature operation te st	Ta = -20 °C, 240 hrs	ours. These defects c an't be accepted:
5	High temperature & high humi dity	Ta = 60 °C, 90%RH, 240 hrs	1.Air bubble 2.Seal leak 3.Non-display
6	Thermal shock(Non-operation)	Ta = -20 °C \leftrightarrow 70°C (0.5 hr), 1hour/Cycle,100 cycle	4.Missing segments 5.Glass crack
7	Shock test (Non-operation)	50G,20ms,half sine Wave,1time for each axis, ±X,Y,Z directions	
8	ESD test(operation)	C=150pF, R=330Ω, Air: ±15KV, 9points, 25times/point; Contact: ±8KV,9points,25times/point	Air: PANEL AA around Contact: BEZEL Class B
9	Vibration Test(Non-operation)	1.5G,10~200Hz,30min/AXI S X,Y,Z directions Wave: random	

Note: After the reliability test, the product only guarantee function normally without any fatal defect (non-display, line defect, abormal display etc.). All the cosmetic specification is judged before the reliablity test.

SPEC. NUMBER	SPEC TITLE		PAGE
S801-5126	XX产品 FG-code Pro	duct Specification	23 OF 31



PRODUCT GROUP REV

TFT LCD PRODUCT

P0

2019.04.16

ISSUE DATE

11.0 Precautions

Please pay attention to the followings when you use this TFT LCD Panel.

- 11.1 Mounting Precautions
- (1) Use fingerstalls with soft gloves in order to keep display clean during the incoming inspection and assembly process.
- (2) You must mount a module using specified mounting holes (Details refer to the drawings).
- (3) Please make sure to avoid external forces applied to the Source PCB or FPC and D-IC during the process of handling or assembling. If not, It causes panel damage or malfunction.
- (4) Note that polarizers are very fragile and could be easily damaged. Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment.
- (5) Do not pull or fold the source D-IC which connect the source PCB or FPC and the panel.
- Do not pull or fold the LED wire.
- (6) After removing the protective film, when the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with alcohol or purified water.
- Do not strong polar solvent because they cause chemical damage to the polarizer.
- (7) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
- (8) Protection film for polarizer on the module shall be slowly peeled off just before use so that the electrostatic charge can be minimized.
- (9) Since the LCD is made of glass, do not apply strong mechanical impact or static load onto it. Handling with care since shock, vibration, and careless handling may seriously affect the product. If it falls from a high place or receives a strong shock, the glass may be broken.
- (10) Do not disassemble the module.
- (11) To determine the optimum mounting angle, refer to the viewing angle range in the specification for each model.
- (12) If the customer's set presses the main parts of the LCD, the LCD may show the abnormal display. But this phenomenon does not mean the malfunction of the LCD and should be pressed by the way of mutual agreement.
- (13)Do not drop water or any chemicals onto the LCD's surface.
- (14)The ITO pad area needs special careful caution because it could be easily corroded.

Do not contact the ITO pad area with HCFC, Soldering flux, Chlorine, Sulfur, saliva or fingerprint. To prevent the ITO corrosion, customers are recommended that the ITO area would be covered by UV or silicon.

注: ① (4)(6)(7)(8) 涉及到Pol相关条目适用于OC/MDL出货产品,针对Q/Single建议将pol改为LCD surface,同时删除第8条 ②第(14)条适用于Q/Single出货产品 (MDL/OC可去除此条)

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	24 OF 31



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

11.2 Operating Precautions

- (1) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- (2) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference.
- (3) The electrochemical reaction caused by DC voltage will lead to LCD degradation, so DC drive should be avoided.
- (4) The LCD modules use C-MOS LSI drivers, so customers are recommended that any unused input terminal would be connected to Vdd or Vss, do not input any signals before power is turn on, and ground you body, work/assembly area, assembly equipments to protect against static electricity.
- (5) Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged.
- (6) Design the length of cable to connect between the connector for back-light and the converter as short as possible and the shorter cable shall be connected directly.

The longer cable between that of back-light and that of converter may cause the luminance of LED to lower and need a higher startup voltage(Vs).

- (7) Connectors are precise devices for connecting PCB and transmitting electrical signals. Operators should insert and unplug MDL in parallel when assembling MDL.
- (8) Do not connect or disconnect the cable to/ from the module at the "Power On" condition.
- (9) When the module is operating, do not lose CLK, ENAB signals. If any one these signals is lost, the LCD panel would be damaged.
- (10) Obey the supply voltage sequence. If wrong sequence is applied, the module would be damaged.
- (11) Do not re-adjust variable resistor or switch etc.
- (12) Long Side LED Bar design is recommended when using E-LED type Back Light (GOA Panel Q /Single/OC出货时填写)

注:

①(1)涉及到Pol相关条目适用于OC/MDL出货产品, ②(6)(7)涉及到connector相关适用于OC/MDL出货产品

11.3 Electrostatic Discharge Control

- (1) Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly. Keep products as far away from static electricity as possible.
- (2) Avoid the use work clothing made of synthetic fibers. We recommend cotton clothing or other conductivity-treated fibers.
- (3) In order to prevent potential problems, Flicker should be adjusted by Optimizing the Vcom value in customer LCM line through the I2C interface.此条适用于Q/Single/OC出货

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	25 OF 31



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

11.4 Precautions for Strong Light Exposure

It is not allowed to store or Operate directly in strong light or in high temperature and humidity for a long time; Strong light exposure causes degradation of polarizer and color filter.

11.5 Storage Precautions


When storing modules as spares for a long time, the following precautions are necessary.

•(1) The polarizer surface should not come in contact with any other object.

It is recommended that they be stored in the container in which they were shipped.

Temperature : $5 \sim 40$ °C

- •(2) Humidity : 35 ~ 75 %RH
- •(3) Period : 6 months
- •(4) Control of ventilation and temperature is necessary.
- •(5) Please make sure to protect the product from strong light exposure, water or moisture. Be careful for condensation.
- •(6) Store in a polyethylene bag with sealed so as not to enter fresh air outside in it.
- •(7)Do not store the LCD near organic solvents or corrosive gasses.
- •(8) Please keep the Modules/OC/FOG at a circumstance shown below Fig.



11.6 Precautions for Protection Film (适用通用产品, 含Q/Single Production)

• (1) Remove the protective film slowly, keeping the removing direction approximate 30-degree not vertical from panel surface, If possible, under ESD control device like ion blower, and

the humidity of working room should be kept over 50%RH to reduce the risk of static charge.

• (2) In handling the LCD, wear non-charged material gloves. And the conducting wrist to the earth and the conducting shoes to the earth are necessary.

11.7 Appropriate Condition for Display

- •(1) Normal operating condition
 - Temperature: $0 \sim 40^{\circ}$ C
 - Operating Ambient Humidity : 10 ~ 90 %
 - Display pattern: dynamic pattern (Real display)
- Suitable operating time: under XX hours a day. (Please contract BOE in advance for 7*24hrs or more than suggested Operating time,每天可使用的小时数需根据不同产品填写)
 - -Long-term lighting products recommended regular shutdown
- •(2) Special operating condition

If the product will be used in extreme conditions such as high temperature, humidity, display patterns or 7*24hrs operation time etc.., It is strongly recommended to contact BOE for Application engineering advice. Otherwise, its reliability and function may not be guaranteed.

•(3)Black image or moving image is strongly recommended as a screen save.

SPEC. NUMBER	SPEC TITLE		PAGE
S801-5126	XX产品 FG-code	Product Specification	26 OF 31



REV

ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

- (4) Lifetime in this spec. is guaranteed only when commercial display is used according to operating usages.
- (5) Please contract BOE in advance when you want to switch between portrait and landscape screen (横竖屏兼容设计可删除此项)
- (6) Please contact BOE in advance for outdoor operation.
- (7) Please contact BOE in advance when you display the same pattern for a long time.
- (8) If the Module keeps displaying the same pattern for a long period of time, the image may be "sticked" to the screen. To avoid image sticking, it is recommended to use a screen saver.
- (9) Do not exceed the absolute maximum rating value. (supply voltage variation, input voltage variation, variation in part contents and environmental temperature, and so on) Otherwise the Module may be damaged.
- (10) Dew drop atmosphere should be avoided.
- (11) The storage room should be equipped with a good ventilation facility and avoid to expose to corrosive gas, which has a temperature controlling system.
- (12) When expose to drastic fluctuation of temperature (hot to cold or cold to hot) ,the LCD may be affected; Specifically, drastic temperature fluctuation from cold to hot ,produces dew on the LCD's surface which may affect the operation of the polarizer and the LCD.
- (13) Response time will be extremely delayed at lower temperature than the operating temperature range and on the other hand at higher temperature LCD may turn black at temperature above its operational range. However those phenomena do not mean malfunction or out of order with the LCD. The LCD will revert to normal operation once the temperature returns to the recommended temperature range for normal operation

11.8 Others

A. LC Leak

- If the liquid crystal material leaks from the panel, it is recommended to wash the LC with acetone or ethanol and then burn it.
- In case of contact with hands, skin or clothes, it has to be washed away thoroughly with soap.
- If LC in mouth, mouth need to be washed, drink plenty of water to induce vomiting and follow medical advice.
- If LC touch eyes, eyes need to be washed with running water at least 15 minutes.

B. Rework

• When returning the module for repair or etc., Please pack the module not to be broken. We recommend to use the original shipping packages.

SPEC. NUMBER	SPEC TITLE	PAGE
S801-5126	XX产品 FG-code Product Specification	27 OF 31



REV

ISSUE DATE


TFT LCD PRODUCT

P0

2019.04.16

12.0 LABEL

(1) Product label




MDLID 编码规则

序列号	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17
代码	Х	X	Р	3	5	2	7	Х	Х	Х	Х	0	0	1	E	E	J
描述	生指	生管 等级 S,A,P,Q 指定 等			年月			FG Code后四位				流水码 36进制(无I和O)					

年: 2015-15, 2016-16 2020---20, 2021---21.....

月: 1~12月→ 1~9, X, Y, Z

(2) High voltage caution label



HIGH VOLTAGE CAUTION

RISK OF ELECTRIC SHOCK, DISCONNECT THE ELECTRIC POWER BEFORE SERVICING

COLD CATHODE FLUORESCENT LAMP IN LCD

PANEL CONTAINS A SMALL AMOUNT

OF MERCURY, PLEASE FOLLOW LOCAL OR-DINANCES OR REGULATIONS FOR DISPOSAL,


SPEC. NUMBER S801-5126

SPEC TITLE

XX产品 FG-code Product Specification

PAGE 28 OF 31

DAS-RD-2020006-O



REV


ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

(3) Box label



Serial number marked part needs to print, show as follows:

- 1. FG-CODE(Before 12 bit): GV185FHM-N10
- 2. Product quantity
- 3. Box ID
- 4. Date
- 5.FG-Code After four---DM30

Total Size:110×55mm

SPEC. NUMBER SPEC TITLE PAGE S801-5126 XX产品 FG-code Product Specification 29 OF 31

DAS-RD-2020006-O



REV


ISSUE DATE

TFT LCD PRODUCT

P0

2019.04.16

13.0 PACKING INFORMATION



将LCM装入PE袋中,并沿产品边缘折叠,再将9pcs套有PE袋的LCM(PCB朝下)依次放入Bottom对应的卡槽内



Step 1



Step 2

将 EPE Cover 盖在 Bottom 上,再将纸箱用胶带封装

容量: 9 LCM/Box, 9 PE Bag/Box

将16ea 封装好的纸箱放到木托上,回字形排布 容量: 144 LCM/Pallet





Step 3

Step 4

放置8ea纸护角,用缠绕裹包 (≥3层) 再用打包带"井"字 形固定 厢车装载方式:两横摆放,单层码放 厢车装载量_12m:3168 pcs (22托)



Step 5



Step 6

SPEC. NUMBER **\$801-5126**

SPEC TITLE

XX产品 FG-code Product Specification

PAGE 30 OF 31

A4(210 X 297)